# Report Information from Dialog DataStar



# **Table of Contents**

ataStar Documents	
Electrical transport properties of CoSi/sub 2/ and NiSi/sub 2/ thin films	
Low-temperature diffusion of silicon atoms in the nickel-nickel silicide-silicon system	
The growth processes of thin film silicides in Si/Ni planar systems	
Formation of Ni silicide from Ni(Au) films on (111)Si	
In-situ investigation of the formation of nickel silicides during interaction of single-crystalline and amorphous silicon with nickel	
earch Strategy	

#### Electrical transport properties of CoSi/sub 2/ and NiSi/sub 2/ thin films.

#### Dialog eLinks

#### Accession number & update

0002267245 20070101

#### Source

Applied Physics Letters, {Appl-Phys-Lett-USA}, 1 May 1984, vol. 44, no. 9, p. 913–15, 11 refs, CODEN: APPLAB, ISSN: 0003-6951, USA.

#### Author(s)

Hensel-J-C, Tung-R-T, Poate-J-M-, Unterwald-F-C.

#### Author affiliation

Hensel, J.C., Tung, R.T., Poate, J.M.., Unterwald, F.C., AT&T Bell Labs., Murray Hill, NJ, USA.

#### Abstract

Transport studies have been performed on thin films of CoSi/sub 2/ and NiSi/sub 2/ in the temperature range 1–300K. The conductivities are metallic with essentially the same temperature dependence; however, the residual resistivities are markedly different even though the two silicides are structurally similar (the room-lemperature resistivity of NiSi/sub 2/ being at least twice that of CoSi/sub 2/ of 15 muOmega cm). The difference is attributed to intrinsic defects in NiSi/sub 2/. This defect has been silicided by ion bombardment of the film where it is also shown that Matthiessen's rule is obeyed over a remarkable range of bombardment doses.

#### Language

English.

Publication year

#### 1984.

Copyright statement Copyright 1984 IEE.

((c) 2008 The Institution of Engineering and Technology)

#### Low-temperature diffusion of silicon atoms in the nickel-nickel silicide-silicon system.

#### Dialog eLinks

Full text options

Accession number & update

0002643349 20070101.

#### Source

Soviet Physics Journal, (Sov-Phys-J-USA), March 1985, vol. 28, no. 3, p. 242-5, CODEN: SOPJAQ, ISSN: 0038-5697, USA. Translation from: Izvestiya Vysshikh Uchebnykh Zavedenii Fizika, (Izv-Vyssh-Uchebn-Zaved-Fiz-USSR), March 1985, vol. 28, no. 3, p. 78-83, CODEN: IVUFAC, ISSN: 0021-3411. Country of publication: USSR.

#### Author(s)

Rodionov-A-I, Uskov-V-A.

#### Author affiliation

Rodionov, A.I., Uskov, V.A., A.A. Zhdanov Gor'kii Polytech. Inst., USSR.

#### Abstract

The diffusion of Si atoms from a silicon substrate through a layer of nickel monosilicide into a Ni film is investigated in the temperature interval 470–670K by the method of radioactive isotopes. The distribution profile of Si in NiSi and Ni is derived. The GB–diffusion parameters of Si in NiSi are determined. It is shown that when T>570K there is an increase in the thickness of the initial NiSi layer, and a kink appears on the 1 n D=f(1/T) curve. The associated change in the activation energy of diffusion from 0.43 470–570K) to 0.72 eV (570–670K) is explained by the formation of Ni–Si and Si–O type

complexes. The diffusion of silicon atoms accompanied by complex- formation processes determines the evolution of the resistivity of the Ni-NiSi-Si contact.

#### Language

English.

Publication year 1985

#### Copyright statement

Copyright 1986 IEE.

((c) 2008 The Institution of Engineering and Technology)

#### The growth processes of thin film silicides in Si/Ni planar systems.

#### Dialog eLinks

Full text options

#### Accession number & update

0002546568 20070101

#### Conference information

Sixth International Conference on 'Thin Films', Stockholm, Sweden,

13-17 Aug. 1984.

#### Source

Thin Solid Films, {Thin-Solid-Films-Switzerland}, 15 March 1985, vol. 125, no. 1-2, p. 71-8, 11 refs. CODEN: THSFAP, ISSN: 0040-6090, Switzerland.

#### Author(s)

Maini-G. Costato-M. Panini-F.

#### Author affiliation

Maini, G., Costato, M., Panini, F., Dept. of Phys., Modena Univ., Italy,

#### **Abstract**

All the compounds predicted from the Si-Ni phase diagram were observed by depositing thin layers of nickel onto silicon in known quantities and ratios to each other using an unreactive substrate such as SiO/sub 2/. After deposition, the samples were annealed in the temperature range 200-750°C and analysed using 2 MeV /sup 4/He/sup positive Rutherford backscattering spectrometry and X-ray diffraction techniques. Ni/sub 2/Si is the first phase formed at a low temperature (about 250°C). Under silicon-rich conditions the system develops in a reproducible manner, subsequently giving rise, when all the nickel was reacted, to the formation of NiSi and of NiSi/sub 2/ by reaction at 750°C of the NiSi with silicon. The kinetic diffusion approach accounts for the formation and sequence of Ni/sub 2/Si and NiSi. The phase Ni/sub 5/Si/sub 2/ forms between Ni/sub 2/Si and nickel under nickel-rich conditions. The phases Ni/sub 3/Si/sub 2/ and Ni/sub 3/Si were observed at 400°C and 450°C respectively.

#### Language

English.

#### Publication year 1985

Copyright statement

Copyright 1985 IEE.

((c) 2008 The Institution of Engineering and Technology)

#### Formation of Ni silicide from Ni(Au) films on (111)Si.

#### Dialog eLinks

Full text options

### Accession number & update

0005277567 20070101.

#### Source

Journal of Applied Physics, {J-Appl-Phys-USA}, 15 April 1996, vol. 79, no. 8, p. 4078-86, 41 refs, CODEN: JAPIAU, ISSN: 0021-8979, Publisher: AIP, USA.

#### Author(s)

Mangelinck-D. Gas-P. Grob-A. Pichaud-B. Thomas-O.

#### Author affiliation

Mangelinck, D., Fac. des Sci. de Saint Jerome, CNRS, Marseille, France.

#### Abstract

The solid state reaction between a Ni (7 at. 98 Au) film and a Si substrate at temperatures ranging from 250 to 800 °C is examined by scanning electron microscopy, X-ray diffraction, and Rutherford backscattering spectrometry. Compared to the usual features for thin film reaction of Ni with Si, we observed the following. (i) The simultaneous growth of Ni/sub 2/Si and NiSi, and the growth of NiSi at the expense of both Ni/sub 2/Si and Ni. This is related to Au accumulation in the metal layer. (ii) Au precipitation at 300 °C followed by the dissolution of the clusters thus created above the Au-Si eutectic temperature (370 °C). (iii) A decrease of the temperature of formation of NiSi/sub 2/s and the appearance of thickness oscillations that are characteristic of nucleation. These different effects are interpreted by taking into account the metallurgy of the system: segregation of Au in the Ni film, Au solubility in the different silicides, change in surface and interface energies, and chemical interactions with Si.

#### Language

English.

#### Publication year

1996.

#### Copyright statement

Copyright 1996 IEE.

((c) 2008 The Institution of Engineering and Technology)

# In-situ investigation of the formation of nickel silicides during interaction of single-crystalline and amorphous silicon with nickel.

#### Dialog eLinks

Full text options (INFIG Full Text Entrieval Options

#### Accession number & update

0006937599 20070101.

#### Source

Journal of Alloys and Compounds, {J-Alloys-Compd-Switzerland}, 26 April 2001, vol. 319, p. 187-95, 23 refs, CODEN: JALCEU, ISSN: 0925-8388. Publisher: Elsevier, Switzerland.

#### Author(s)

Bokhonov-B, Korchagin-M.

#### Author affiliation

Bokhonov, B., Korchagin, M., Inst. of Solid State Chem., Acad. of Sci., Novosibirsk, Russia.

#### Abstract

In situ investigations showed that the sequence of phase formation during interaction of nickel particles with single crystalline (100) silicon and amorphous silicon corresponds to the following sequence of stages during the annealing of thin-film systems: (a) within a temperature range up to 500°C, the first and prevailing phase formed is Ni/sub 2/Si; and (b) annealing at temperatures above 600°C is accompanied by the formation and epitaxial growth of the NiSi/sub 2/ phase. The growth of the nickel disilicide crystalline phase is accompanied by the formation of dislocations both in the nickel disilicide phase and in the silicon phase. The interaction of the amorphous silicion film with nickel particles at temperatures above 600°C leads to the crystallization of several silicide phases: NISI/sub 2/, NISI, NI/sub 3/Si/sub 2/. The formation of silicide phases due to the interaction of nickel particles with silicon during annealing did not confirm the formation of an intermediate amorphous silicide that was observed earlier in thin-film nickel-gilicon systems. Irradiation with a beam of accelerated electrons in a

microscope leads to an increase of the rate of silicide phase formation and to a decrease of the temperature at which the nicked dislilicide phase is formed epitaxially, at least to 400°C. In our opinion, the observed effect can be due to the formation of defects in the structure of single crystalline silicon.

Language English.

Publication year

2001.

Copyright statement Copyright 2001 IEE.

((c) 2008 The Institution of Engineering and Technology)

## Search Strategy

No.	Database	Search term	Info added since	Results
1	INZZ	(nickel ADJ monosilicide OR NISI) AND (layer OR film) AND ratio AND temperature AND amorphous	unrestricted	5
2	INZZ	(nickel ADJ monosilicide OR NiSi) AND (layer OR film) AND temperature	unrestricted	575
3	INZZ	2 AND (Nickel OR Ni)	unrestricted	554
4	INZZ	3 AND (Si OR silicon)	unrestricted	531
5	INZZ	4 AND (anneal* OR (thermal OR heat) ADJ treatment)	unrestricted	28
6	INZZ	3 AND amorphous	unrestricted	116
7	INZZ	4 AND amorphous	unrestricted	116

Saved: 26-Apr-2008 02:07:04 MEST